

Head Office: 101-102, Kaveri Complex, Jagannath Mandir Road, Sakinaka Junction, Mumbai - 400 072 Phone: :+91-22-2850 6586, 2850 6532 Fax:+91-22-2852 5954 Website: www.anupamcoloursacci.com E-mail: info@anupamcoloursacci.com

ANUTHERM "GOLDEN YELLOW" M-15

ANUTHERM M-15 is a monoclinic Lead Chromate. This Pigment is highly stabilized and is stable at high temperatures. Therefore, it is highly suitable for use in Plastic Master Batches. This product finds regular use in the manufacture of Plastic Masterbatches where processing temperature are in the range of 240°C - 250°C.

TECHNICAL DATA

Colour Index No.	77603					
Colour Index Pigment No.	Y-34					
Oil Absorption	25-30					
Specific Gravity	5.0-5.4					
Bulk Density g/cc	0.65					
BLEEDING IN						
Water	5					
5% Caustic Soda	3					
5% Hydrochloric Acid	3					
Linseed Oil	5					
Ethanol	5					
Ethyl Acetate	5					
Xylene	5					
n-Butanol	5					
Methyl Ethyl Ketone	5					
Mineral Turpentine	5					
Cellosolve	5					
Dioctyl Phthalate	5					
RESISTANCE TO HEAT						
120°C / 30 min.	SB					
150°C / 20 min.	SB					
180°C / 10 min.	SB					
210°C / 10 min.	SB					
RESISTANCE TO LIGHT						
Full Tone	7					
Tint Tone (1:10)	6					
RESISTANCE TO	RESISTANCE TO					
Acid	G					
Alkali	Р					
APPLICATIONS						
Paints	*					
Printing Inks						
Rubber						
Leather Pastes	*					
Linoleum						
PVC Leather Cloth	*					
Paper Coating						
Chalk / Crayons						
Plastics	*					

LEGEND

COLOUR	BLEEDING	HEAT STABILITY	LIGHTFASTNES	S APPLICATIONS	E - EXCELLENT
Y - YELLO	W SCALE (1-5)	SB:STABLE	SCALE (1-8)	*:RECOMMENDED/	VG – VERY GOOD
R - RED	5:NO BLEED	USB: UNSTABLE	1 – POOR	MAYBE USED	G -GOOD
W – WHITE	1:CONSIDERA	BLE BLEED	8 – EXCELLENT		F - FAIR
					P - POOR