

ANUPAM COLOURS & CHEMICALS INDUSTRIES

Head Office: 101-102, Kaveri Complex, Jagannath Mandir Road, Sakinaka Junction, Mumbai - 400 072
Phone: :+91-22-2850 6586, 2850 6532 Fax:+91-22-2852 5954
Website: www.anupamcoloursacci.com E-mail: info@anupamcoloursacci.com

ANUTHERM "LEMON YELLOW" L-25

ANUTHERM Lemon Yellow L-25 is a monoclinic Lead Chromate material. This pigment is highly stabilized and is stable at high temperatures. Therefore, it is suitable for use in Plastic Master Batches where the process demands pigments to give satisfactory performance at process temperature of 240°C - 250°C.

TECHNICAL DATA

Colour Index No.	77603					
Colour Index Pigment No.	Y-34					
Oil Absorption	15-20					
Specific Gravity	4.9-6.0					
Bulk Density g/cc	0.70					
BLEEDING IN (1-Poor 5-Excellent)						
Water	5					
5% Caustic Soda	3					
5% Hydrochloric Acid	3					
Linseed Oil	5					
Ethanol	5					
Ethyl Acetate	5					
Xylene	5					
n-Butanol	5					
Methyl Ethyl Ketone	5					
Mineral Turpentine	5					
Cellosolve	5					
Dioctyl Phthalate	5					
RESISTANCE TO HEAT						
120°C / 30 min.	SB					
150°C / 20 min.	SB					
180°C / 10 min.	SB					
210°C / 10 min.	SB					
RESISTANCE TO LIGHT						
Full Tone	4					
Tint Tone (1:10)	5					
RESISTANCE TO						
Acid	G					
Alkali	Р					
APPLICATIONS						
Paints	*					
Printing Inks						
Rubber						
Leather Pastes	*					
Linoleum						
PVC Leather Cloth	*					
Paper Coating						
Chalk / Crayons						
Plastics *						

LEGEND

COLOUR	BLEEDING	HEAT STABILITY	LIGHTFASTNESS	APPLICATIONS	E – EXCELLENT
Y – YELLOW	SCALE (1-5)	SB: STABLE	SCALE (1-8)	* :RECOMMENDED/	VG – VERY GOOD
R – RED	5:NO BLEED	USB: UNSTABLE	1 – POOR	MAYBE USED	G - GOOD
W – WHITE	WHITE 1:CONSIDERABLE BLEED		8 – EXCELLENT		F – FAIR
					P – POOR