Head Office: 101-102, Kaveri Complex, Jagannath Mandir Road, Sakinaka Junction, Mumbai - 400 072
Phone: :+91-22-2850 6586, 2850 6532 Fax:+91-22-2852 5954
Website: www.anupamcoloursacci.com E-mail: info@anupamcoloursacci.com

ANUCHROME "LEMON CHROME" L-26

ANUCHROME L-26 is a monoclinic lead chromate and is a raw material for the Paint industry. This is an economical grade in Lemon Chromes product range. This pigment is stabilized one and it generally offers good fastness to light and weather. This pigment has fair dispersion characteristics.

TECHNICAL DATA

Colour Index No.	77603					
Colour Index Pigment No.	Y-34					
Oil Absorption	16-21					
Specific Gravity	4.9-6.0					
Bulk Density g/cc	1.03					
BLEEDING IN (1-Poor 5-Excellent)						
Water	5					
5% Caustic Soda	3					
5% Hydrochloric Acid	3					
Linseed Oil	5					
Ethanol	5					
Ethyl Acetate	5					
Xylene	5					
n-Butanol	5					
Methyl Ethyl Ketone	5					
Mineral Turpentine	5					
Cellosolve	5					
Dioctyl Phthalate	5					
RESISTANCE TO HEAT						
120°C / 30 min.	SB					
150°C / 20 min.	SB					
180°C / 10 min.	SB					
210°C / 10 min.	SB					
RESISTANCE TO LIGHT						
Full Tone	4					
Tint Tone (1:10)	5					
RESISTANCE TO						
Acid	G					
Alkali	Р					
APPLICATIONS						
Paints	*					
Printing Inks	*					
Rubber						
Leather Pastes	*					
Linoleum	*					
PVC Leather Cloth	*					
Paper Coating *						
Chalk / Crayons						
Plastics *						

LEGEND

COLOUR	BLEEDING	HEAT STABILITY	LIGHTFASTNESS	APPLICATIONS	E - EXCELLENT	
Y - YELLOW	SCALE (1-5)	SB: STABLE	SCALE (1-8)	* :RECOMMENDED/	VG – VERY GOOD	
R - RED	5:NO BLEED	USB: UNSTABLE	1 – POOR	MAYBE USED	G - GOOD	
W - WHITE	1:CONSIDERABLE BLEED		BLE BLEED 8 – EXCELLENT		F – FAIR	
				P = POOR		